

OdePkg

A package for solving differential equations with Octave
This document currently is under development

by Thomas Treichl

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or any later version published by the Free Software Foundation; with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts. A copy of the license is included in the section entitled "GNU Free Documentation License".

Table of Contents

1	Beginner’s Guide	1
1.1	About OdePkg	1
1.2	OdePkg history and roadmap	1
1.3	Installation and deinstallation	2
1.4	Reporting Bugs	2
1.5	First tests and demos	2
2	User’s Guide	4
2.1	Solver families	4
2.1.1	M-file Runge–Kutta solvers	4
2.1.2	Mex-file Hairer–Wanner solvers	5
2.1.3	Other solvers	5
2.1.4	ODE solver performances	5
2.2	ODE/DAE options	6
3	Coder’s Guide	12
3.1	C Mex Function Reference	12
	Appendix A	14
A.1	GNU Free Documentation License	14

1 Beginner's Guide

The “Beginner's Guide” is intended for new users who want to solve differential equations with the higher level language Octave and the toolbox OdePkg. In this chapter it will be explained what OdePkg is about in Section 1.1 [About OdePkg], page 1 and how OdePkg grew up from the beginning in Section 1.2 [OdePkg history and roadmap], page 1. In Section 1.3 [Installation and deinstallation], page 2 it is explained how OdePkg can be installed and in Section 1.5 [First tests and demos], page 2 the first examples are explained.

1.1 About OdePkg

OdePkg is part of the **GNU Octave Repository** (resp. the Octave–Forge project) that was initiated by Paul Kienzle in the year 2000 and that is hosted at <http://octave.sourceforge.net>. The package includes commands for setting up various options, output functions etc. before solving a set of differential equations with the solver functions that are also included. OdePkg formerly was initiated to solve explicitly formulated ordinary differential equations (ODEs) only, but there are already improvements so that differential algebraic equations (DAEs) in explicit form can also be solved. At this time OdePkg is under development with the main target, to make a package that is mostly compatible to commercial solver products.

1.2 OdePkg history and roadmap

- | | |
|--------------------------------|--|
| OdePkg Version 0.0.1 | The initial release was already a modification of the old “ode package” that was hosted at Octave–Forge and that was written by Marc Compere some when between 2000 and 2001. The four variable step–size Runge–Kutta algorithms in three solver files and the three fixed step–size solvers have been merged. It was possible to set some options for these solvers. The four output–functions (<code>odeprint</code> , <code>odeplot</code> , <code>odephas2</code> and <code>odephas3</code>) have been added along with other examples that initially have not been there. |
| OdePkg Version 0.1.x | The major milestone along versions 0.1.x was that four stable solvers have been implemented (ie. <code>ode23</code> , <code>ode45</code> , <code>ode54</code> and <code>ode78</code>) supporting all options that can be set for these kind of solvers and also all necessary functions for setting their options (eg. <code>odeset</code> , <code>odepkg_structure_check</code> , etc.). Since version 0.1.3 there is also code available that interfaces the Fortran solver ‘ <code>dopri5.f</code> ’ that is written by Ernst Hairer and Gerhard Wanner (cf. ‘ <code>odepkg_mexsolver_dopri5.c</code> ’ and the helper files ‘ <code>odepkgext.c</code> ’ and ‘ <code>odepkgmex.c</code> ’). |
| OdePkg Version 0.2.x | The main work along version 0.2.x was making the interface functions for the non–stiff and stiff solvers from Ernst Hairer and Gerhard Wanner enough stable so that they could be compiled and installed by default. Wrapper functions have been added to the package with help texts and tests (eg. <code>ode2r</code> , <code>ode5r</code> , <code>oders</code> etc.). Six testsuite functions have been added for performance tests of the different solvers (<code>odepkg_testsuite_chemakzo</code> , <code>odepkg_testsuite_oregonator</code> , <code>odepkg_testsuite_transistor</code> , etc.). |
| (current) Version 0.3.x | Ongoing work with this manual. Fetching and adding DDE–solvers from Netlib or Ernst Hairer or Jeff Cash if GPL compatible. |
| (future) Version 0.4.x | Ongoing work with this manual. Fetching and adding IDE–solvers from Netlib or Ernst Hairer or Jeff Cash if GPL compatible. |
| (future) Version 0.5.x | (Maybe) A lot of compatibility tests. |

(future) Version 0.6.x (Maybe) Final release before version 1.0.0.
 (future) Version 1.0.0 Completed odepkg release 1.0.0 with m-solvers and mex-solvers.

1.3 Installation and deinstallation

OdePkg can be installed easily using the `pkg` command of Octave. For this get into the directory where the current release of OdePkg can be found, start `octave` and type

```
pkg install odepkg-x.x.x.tar.gz
```

where 'x.x.x' in the name of the '*.tar.gz' file is the current release number of OdePkg that is available. If you want to deinstall resp. remove OdePkg then simply type

```
pkg uninstall odepkg-x.x.x.tar.gz
```

If you encounter problems during the installation process of OdePkg with the `pkg` command or if you have an OdePkg that seems to be broken then please report this on the mailing-list of Octave-Forge using the email address `octave-dev@lists.sourceforge.net`.

1.4 Reporting Bugs

If you encounter problems while using OdePkg or if you find bugs in the source codes then please report that via email at the Octave-Forge mailing-list using the email address `octave-dev@lists.sourceforge.net` and directly send a copy to the email address `treichl@users.sourceforge.net`.

1.5 First tests and demos

Let's have a look at the first ordinary differential equation with the name "foo". The "foo" equation of second order may be of the form $y''(t) + C_1 y'(t) + C_2 y(t) = C_3$. With the substitutions $y_1(t) = y(t)$ and $y_2(t) = y'(t)$ this differential equation of second order can be split into two differential equations of first order, ie. $y_1'(t) = y_2(t)$ and $y_2'(t) = -C_1 y_2(t) - C_2 y_1(t) + C_3$. Next the numerical values for the constants need to be defined, ie. $C_1 = 2.0$, $C_2 = 5.0$, $C_3 = 10.0$. This set of ordinary differential equations can now be written as an Octave function like

```
function vdy = foo (vt, vy, varargin)
    vdy(1,1) = vy(2);
    vdy(2,1) = - 2.0 * vy(2) - 5.0 * vy(1) + 10.0;
endfunction
```

It is seen that this ODEs do not depend on time, nevertheless the first input argument of this function needs to be defined as the time argument, followed by a integrated state argument `vy` and a variable size input argument `varargin` that can be used to set up user defined constants or control variables. As it is known that "foo" is a set of *ordinary* differential equations we can choose one of the four m-file Runge-Kutta solvers (cf. Section 2.1 [Solver families], page 4). It is also known that the time period of interest may be between $t_0 = 0.0$ and $t_e = 5.0$ as well as that the initial values of the ODEs are $y_1(t = 0) = 0.0$ and $y_2(t = 0) = 0.0$. Solving this set of ODEs can be done by typing the following commands in the Octave interpreter window

```
ode45 (@foo, [0 5], [0 0]);
```

A figure window opens and it can be seen how this ODEs are solved from $t_0 = 0.0$ to $t_e = 5.0$. If opening the figure window is unwanted then output arguments have to be used to catch the results of the solving process, eg.

```
[t, y] = ode45 (@foo, [0 5], [0 0]);
```

Results can also be obtained as a Octave structure if one output argument is used like in the following example. Then the results are stored in the fields `S.x` and `S.y`.

```
S = ode45 (@foo, [0 5], [0 0]);
```

As noticed before, a function for the ordinary differential equations must not be rewritten all the time if some of the parameters are going to change, that's what the input argument `varargin` is for. So rewrite the function `foo` into `newfoo` the following way

```
function vdy = newfoo (vt, vy, varargin)
    vdy(1,1) = vy(2);
    vdy(2,1) = -varargin{1}*vy(2)-varargin{2}*vy(1)+varargin{3};
endfunction
```

There is nothing said about the constant values anymore, but if using the following caller routine in the Octave interpreter window then the same results can be obtained as before (ie. the parameters are directly feed through from the caller routine to the function `newfoo`).

```
ode45 (@newfoo, [0 5], [0 0], 2.0, 5.0, 10.0);
```

The OdePkg can do much more while solving ODEs and DAEs, eg. you can set up other output functions instead of the function `odeplot`. So as a last example in this beginning chapter it is shown how this can be done, ie. with the command `odeset`

```
A = odeset ('OutputFcn', @odeprint);
ode45 (@newfoo, [0 5], [0 0], A, 2.0, 5.0, 10.0);
```

The options structure `A` that can be set up with with the command `odeset` must always be the fourth input argument when using the ODE-solvers and the DAE-solvers (read the help files for the other solvers if there may be changes in the future). The options that can be set are described in Section 2.2 [ODE/DAE options], page 6.

Other examples have also been added to the OdePkg. These example files and functions are of the form `odepkg_equations_*`. Demos have been added to these functions as well so their functionality can be viewed very quickly.

Before you continue reading the next chapter notice that nearly every function that belongs to the OdePkg has its own help description and demos, so you can have a look for yourself how the different functions can be used. If you want to have a look at the help description then type

```
help fcname
```

in the Octave interpreter window where `fcname` is the name of the function for the help description to be viewed. Type

```
demo fcname
```

in the Octave interpreter window where `fcname` is the name of the function of the demo to run. Last but not least write

```
doc odepkg
```

for opening this manual in the texinfo reader of the octave interpreter window.

2 User's Guide

The "User's Guide" is intended for trained users who already do know in principal how to solve differential equations with the higher level language Octave and OdePkg. In this chapter it will be explained which solvers can be used for the different kind of problems in Section 2.1 [Solver families], page 4 and which options can be set for the optimization of the solving process in Section 2.2 [ODE/DAE options], page 6.

2.1 Solver families

In this section the different kinds of solvers are explained. It starts with the standard M-file Runge-Kutta solvers in section Section 2.1.1 [M-file Runge-Kutta solvers], page 4 and then it is continued with the Mex-file Hairer-Wanner solvers in section Section 2.1.2 [Mex-file Hairer-Wanner solvers], page 5. Other solvers are described in section Section 2.1.3 [Other solvers], page 5. Performance tests have also been added to the OdePkg. Some of these performance results have been added to section Section 2.1.4 [ODE solver performances], page 5.

2.1.1 M-file Runge-Kutta solvers

The M-file Runge-Kutta solvers are written in the Octave interpreter language and are stored '`*.m`' files. There have been implemented four different solvers of similiar structure and types, ie. `ode23`, `ode45`, `ode54` and `ode78`¹.

The order of all of the following Runge-Kutta methods is the order of the local truncation error, which is the principle error term in the portion of the Taylor series expansion that gets dropped, or intentionally truncated. This is different from the local error which is the difference between the estimated solution and the actual, or true solution. The local error is used in stepsize selection and may be approximated by the difference between two estimates of different order, $l(h) = x(O(h+1)) - x(O(h))$. With this definition, the local error will be as large as the error in the lower order method. The local truncation error is within the group of terms that gets multiplied by h when solving for a solution from the general Runge-Kutta method. Therefore, the order- p solution created by the Runge-Kunge method will be roughly accurate to $O(h^{(p+1)})$ since the local truncation error shows up in the solution as $e = hd$, which is h times an $O(h^p)$ term, or rather $O(h^{(p+1)})$.

ode23 Integrates a system of ordinary differential equations using second and third order Runge-Kutta formulas. This particular third order method reduces to Simpson's 1/3 rule and uses the third order estimation for the output solutions. Third order accurate Runge-Kutta methods have local and global errors of $O(h^4)$ and $O(h^3)$ respectively and yield exact results when the solution is a cubic (the variable h is the step size from one integration step to another integration step). This solver requires three function evaluations per integration step.

ode45 Integrates a system of ordinary differential equations using fourth and fifth order embedded formulas from Fehlberg. This is a fourth-order accurate integrator therefore the local error normally expected is $O(h^5)$. However, because this particular implementation uses the fifth-order estimate for x_{out} (ie. local extrapolation) moving forward with the fifth-order estimate should yield local error of $O(h^6)$. This solver requires six function evaluations per integration step.

¹ The descriptions for these Runge-Kutta solvers have been taken from the help texts of the initial m-file Runge-Kutta solvers that were written by Marc Compere, he also pointed out that "a relevant discussion on step size choice can be found on page 90ff in U.M. Ascher, L.R. Petzold, Computer Methods for Ordinary Differential Equations and Differential-Algebraic Equations, Society for Industrial and Applied Mathematics (SIAM), Philadelphia, 1998".

- ode54** The Fehlberg 4(5) of the `ode45` pair is established and works well, however, the Dormand–Prince 4(5) pair minimizes the local truncation error in the fifth–order estimate which is what is used to step forward (local extrapolation). Generally it produces more accurate results and costs roughly the same computationally. This solver requires seven function evaluations per integration step.
- ode78** Integrates a system of ordinary differential equations using seventh and eighth order Runge–Kutta formulas. This is a seventh–order accurate integrator therefore the local error normally expected is $O(h^8)$. However, because this particular implementation uses the eighth–order estimate for x_{out} moving forward with the eighth–order estimate will yield errors on the order of $O(h^9)$. This solver requires thirteen function evaluations per integration step.

2.1.2 Mex–file Hairer–Wanner solvers

The mex–file Hairer–Wanner solvers are written in Fortran (hosted at <http://www.unige.ch/~hairer>) and have been added to the OdePkg as a compressed file with the name ‘`hairer.tgz`’. The licence of these solvers is a modified BSD license (without advertising clause) and can be found as ‘`licence.txt`’ file in the ‘`hairer.tgz`’ package and therefore the Fortran files are GPL compatible. Papers and other details about these solvers can be found at the host adress.

Interface functions for these solvers have been created and have been added to the OdePkg. Their names are ‘`odepkg_mexsolver_xxx.c`’ where ‘`xxx`’ is the name of the Fortran file that is interfaced. The corresponding ‘`odepkg_mexsolver_xxx.mex`’ files are created automatically when installing OdePkg with the `pkg` command, but can also be build manually with the instructions given as a preamble of every ‘`odepkg_mexsolver_xxx.c`’ file.

To provide a shorter name to access these solver functions also wrapper functions have been added that do link to the interface functions, eg. the command `oderd` links to the interface functions `odepkg_mexsolver_radau` and should do exactly the same. Another reason of adding wrapper functions was that help texts, demos and tests cannot be added to the ‘`odepkg_mexsolver_xxx.c`’ files. For accessing the help texts, demos and tests for one of these solvers you should therefore always use the name of the wrapper function, eg. `help oderd`.

The mex–file Hairer–Wanner solvers have been added to the OdePkg to also solve stiff ordinary differential equations that cannot be solved with one of the m–file Runge–Kutta solvers. The following table gives an overview about which solver can be used for the different kind of problems.

ODE–Problem	Solver name	Wrapper file	Interface file	Fortran file
Non–stiff	DOPRI5	‘ <code>ode5d.m</code> ’	‘ <code>odepkg_mexsolver_dopri5.c</code> ’	‘ <code>dopri5.f</code> ’
Non–stiff	DOP853	‘ <code>ode8d.m</code> ’	‘ <code>odepkg_mexsolver_dop853.c</code> ’	‘ <code>dop853.f</code> ’
Non–stiff	ODEX	‘ <code>odeox.m</code> ’	‘ <code>odepkg_mexsolver_odex.c</code> ’	‘ <code>odex.f</code> ’
Stiff	RADAU	‘ <code>ode2r.m</code> ’	‘ <code>odepkg_mexsolver_radau.c</code> ’	‘ <code>radau.f</code> ’
Stiff	RADAU5	‘ <code>ode5r.m</code> ’	‘ <code>odepkg_mexsolver_radau5.c</code> ’	‘ <code>radau5.f</code> ’
Stiff	RODAS	‘ <code>oders.m</code> ’	‘ <code>odepkg_mexsolver_rodas.c</code> ’	‘ <code>rodas.f</code> ’
Stiff	SEULEX	‘ <code>odesx.m</code> ’	‘ <code>odepkg_mexsolver_seulex.c</code> ’	‘ <code>seulex.f</code> ’

Overview about Fortran, Interface and Wrapper files for Hairer–Wanner solvers.

2.1.3 Other solvers

2.1.4 ODE solver performances

```
>> odepkg ('odepkg_performance_mathires');
```

```
-----
```

Solver	RelTol	AbsTol	Init	Mescd	Scd	Steps	Accept	FEval	JEval	LUdec	Time
ode113	1e-007	1e-007	1e-009	7.57	5.37	24317	21442	45760			11.697
ode23	1e-007	1e-007	1e-009	7.23	5.03	13876	13862	41629			2.634
ode45	1e-007	1e-007	1e-009	7.91	5.70	11017	10412	66103			2.994
ode15s	1e-007	1e-007	1e-009	7.15	4.95	290	273	534	8	59	0.070
ode23s	1e-007	1e-007	1e-009	6.24	4.03	702	702	2107	702	702	0.161
ode23t	1e-007	1e-007	1e-009	6.00	3.79	892	886	1103	5	72	0.180
ode23tb	1e-007	1e-007	1e-009	5.85	3.65	735	731	2011	5	66	0.230

```
-----
```

```
octave:1> odepkg ('odepkg_performance_octavehires');
```

```
-----
```

Solver	RelTol	AbsTol	Init	Mescd	Scd	Steps	Accept	FEval	JEval	LUdec	Time
ode23	1e-07	1e-07	1e-09	7.95	5.53	16179	13646	48534			168.182
ode45	1e-07	1e-07	1e-09	8.06	5.64	9401	9398	56400			134.011
ode54	1e-07	1e-07	1e-09	8.31	5.89	8854	7697	61971			127.261
ode78	1e-07	1e-07	1e-09	9.06	6.64	7287	6613	94718			168.769
odeox	1e-07	1e-07	1e-09	6.67	4.25	10969	8881	194129			226.890
ode5d	1e-07	1e-07	1e-09	0.14	-2.28	1014	1014	6086			6.775
ode8d	1e-07	1e-07	1e-09	0.16	-2.26	1046	1030	15385			17.602
ode2r	1e-07	1e-07	1e-09	7.69	5.27	59	59	849	50	59	1.231
ode5r	1e-07	1e-07	1e-09	7.55	5.13	81	81	671	71	81	1.380
odesx	1e-07	1e-07	1e-09	6.63	4.21	39	37	1135	27	190	1.782
orders	1e-07	1e-07	1e-09	7.08	4.66	138	138	828	138	138	2.071

```
-----
```

```
>> odepkg ('odepkg_performance_matchemakzo');
```

```
-----
```

Solver	RelTol	AbsTol	Init	Mescd	Scd	Steps	Accept	FEval	JEval	LUdec	Time
ode113	1e-007	1e-007	1e-007	NaN	Inf	-	-	-	-	-	-
ode23	1e-007	1e-007	1e-007	NaN	Inf	15	15	47			0.431
ode45	1e-007	1e-007	1e-007	NaN	Inf	15	15	92			0.170
ode15s	1e-007	1e-007	1e-007	7.04	6.20	161	154		4	35	0.521
ode23s	1e-007	1e-007	1e-007	7.61	6.77	1676	1676	5029	1676	1677	2.704
ode23t	1e-007	1e-007	1e-007	5.95	5.11	406	404		3	39	0.611
ode23tb	1e-007	1e-007	1e-007	NaN	Inf	607		3036	1	608	6.730

```
-----
```

```
octave:1> odepkg ('odepkg_performance_octavechemakzo');
```

```
-----
```

Solver	RelTol	AbsTol	Init	Mescd	Scd	Steps	Accept	FEval	JEval	LUdec	Time
ode23	1e-07	1e-07	1e-07	0.45	-0.43	432	385	1293			2.926
ode45	1e-07	1e-07	1e-07	0.45	-0.43	277	238	1656			3.087
ode54	1e-07	1e-07	1e-07	0.45	-0.43	216	214	1505			2.769
ode78	1e-07	1e-07	1e-07	0.45	-0.43	210	170	2717			4.700
ode78	1e-07	1e-07	1e-07	2.94	2.05	193	160	4815			6.150
ode5d	1e-07	1e-07	1e-07	2.95	2.06	234	234	1406			1.499
ode8d	1e-07	1e-07	1e-07	2.95	2.06	161	142	2056			2.149
ode2r	1e-07	1e-07	1e-07	8.50	7.57	43	43	372	39	43	0.486
ode5r	1e-07	1e-07	1e-07	8.50	7.57	43	43	372	39	43	0.491
odesx	1e-07	1e-07	1e-07	7.46	6.53	22	22	502	19	96	0.597
orders	1e-07	1e-07	1e-07	7.92	7.04	68	67	401	66	67	0.642

```
-----
```

2.2 ODE/DAE options

The default values of `odeset` can be displayed if `odeset` is called without any input argument and one output argument argument, eg. the following way

```
A = odeset ();
disp (A);
```

'RelTol' The option **'RelTol'** is used to set the relative error tolerance for the error estimation of the solver while solving. It can either be a positive scalar or a vector with every element of the vector being a positive scalar (this depends on the solver that is used). The definite error estimation equation also depends on the solver that is used, but generalized it may be of the form $e(t) = \max(\text{RelTol}^T y(t), \text{AbsTol})$. Run

```
A = odeset ('RelTol', 1, 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], A);
B = odeset ('RelTol', 1e-10, 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], B);
```

to see the effect of using different values for the option **'RelTol'**.

'AbsTol' The option **'AbsTol'** is used to set the absolute error tolerance for the error estimation of the solver while solving. It can either be a positive scalar or a vector with every element of the vector being a positive scalar (this depends on the solver that is used). The definite error estimation equation also depends on the solver that is used, but generalized it may be of the form $e(t) = \max(\text{RelTol}^T y(t), \text{AbsTol})$. Run

```
A = odeset ('AbsTol', 1e-3, 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], A);
B = odeset ('AbsTol', 1e-10, 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], B);
```

to see the effect of using different values for the option **'AbsTol'**.

'NormControl'

The option **'NormControl'** is used to set the type of error tolerance calculation of the solver while solving. It can either be the string **'on'** or **'off'**. At the time the solver starts the initialization procedure a warning message may be displayed if the solver will ignore the **'on'** setting of this option because of an unhandled resp. missing implementation. The definite error estimation equation if set **'on'** also depends on the solver that is used, but generalized it may be of the form $e(t) = \max(\text{RelTol}^T \max(\text{norm}(y(t), \text{Inf})), \text{AbsTol})$. Run

```
A = odeset ('NormControl', 'on', 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], A);
B = odeset ('NormControl', 'off', 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], B);
```

to see the effect of using different values for the option **'NormControl'**.

'MaxStep' The option **'MaxStep'** is used to set the maximum step size for the solver that is used while solving. It can only be a positive scalar. By default this value is set internally by every solver and also may be different when using different solvers. Run

```
A = odeset ('MaxStep', 10, 'OutputFcn', @odeprint);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], A);
B = odeset ('MaxStep', 1e-1, 'OutputFcn', @odeprint);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], B);
```

to see the effect of using different values for the option **'MaxStep'**.

'InitialStep'

The option **'InitialStep'** is used to set the initial first step size for the solver. It can only be a positive scalar. By default this value is set internally by every solver and also may be different when using different solvers. Run

```
A = odeset ('InitialStep', 1, 'OutputFcn', @odeprint);
ode78 (@odepkg_equations_vanderpol, [0 1], [2 0], A);
B = odeset ('InitialStep', 1e-5, 'OutputFcn', @odeprint);
```

```
ode78 (@odepkg_equations_vanderpol, [0 1], [2 0], B);
```

to see the effect of using different values for the option 'InitialStep'.

'InitialSlope'

The option 'InitialSlope' is not handled by any of the solvers by now.

'OutputFcn'

The option 'OutputFcn' can be used to set up an output function for displaying the results of the solver while solving. It must be a function handle to a valid function. There are four predefined output functions available with OdePkg. `odeprint` prints the actual time values and results in the octave window while solving, `odeplot` plots the results over time in a new figure window while solving, `odephas2` plots the first result over the second result as a two-dimensional plot while solving and `odephas3` plots the first result over the second result over the third result as a three-dimensional plot while solving. Run

```
A = odeset ('OutputFcn', @odeprint);
ode78 (@odepkg_equations_vanderpol, [0 2], [2 0], A);
```

to see the effect of using an output function with the option 'OutputFcn'. User defined output functions can also be used. A typical framework for a self-made output function may then be of the form

```
function [vret] = odeoutput (vt, vy, vdec, varargin)
    switch vdec
        case 'init'
            ## Do everything needed to initialize output function
        case 'calc'
            ## Do everything needed to create output
        case 'done'
            ## Do everything needed to clean up output function
    endswitch
endfunction
```

The output function `odeplot` is also set automatically if the solver calculation routine is called without any output argument. Run

```
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0]);
```

to see an example.

'Refine'

The option 'Refine' is used to set the interpolation factor that is used to increase the quality for the output values if an output function is also set with the option 'OutputFcn'. It can only be a integer value $0 \leq \text{Refine} \leq 5$. Run

```
A = odeset ('Refine', 0, 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], A);
B = odeset ('Refine', 3, 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], B);
```

to see the effect of using different values for the option 'Refine'.

'OutputSel'

The option 'OutputSel' is used to set the components for which output has to be performed if an output function is also set with the option 'OutputFcn'. It can only be a vector of integer values. Run

```
A = odeset ('OutputSel', [1, 2], 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], A);
B = odeset ('OutputSel', [2], 'OutputFcn', @odeplot);
ode78 (@odepkg_equations_vanderpol, [0 20], [2 0], B);
```

to see the effect of using different values for the option 'OutputSel'.

'Stats' The option 'Stats' is used to print cost statistics about the solving process after solving has been finished. It can either be the string 'on' or 'off'. Run

```
A = odeset ('Stats', 'off');
[a, b] = ode78 (@odepkg_equations_vanderpol, [0 2], [2 0], A);
B = odeset ('Stats', 'on');
[c, d] = ode78 (@odepkg_equations_vanderpol, [0 2], [2 0], B);
```

to see the effect of using different values for the option 'Stats'. The cost statistics can also be obtained if the solver calculation routine is called with one output argument. The cost statistics then are in the output structure in field 'stats'. Run

```
A = odeset ('Stats', 'on');
B = ode78 (@odepkg_equations_vanderpol, [0 2], [2 0], A);
disp (B);
```

to see an example.

'Jacobian'

The option 'Jacobian' can be used to set up an external Jacobian function or Jacobian matrix for DAE solvers to achieve faster and better results (ODE Runge-Kutta solvers do not need to handle a Jacobian function handle or Jacobian matrix). It must either be a function handle to a valid function or a full constant matrix of size squared the dimension of the set of differential equations. Run

```
function vdy = fpol (vt, vy, varargin)
    vdy = [vy(2); (1 - vy(1)^2) * vy(2) - vy(1)];
endfunction
```

```
function vr = fjac (vt, vy, varargin)
    vr = [0, 1; ...
        -1-2*vy(1)*vy(2), 1-vy(1)^2];
endfunction
```

```
A = odeset ('Stats', 'on');
B = odepkg_mexsolver_radau (@fpol, [0 20], [2 0], A);
C = odeset ('Jacobian', @fjac, 'Stats', 'on');
D = odepkg_mexsolver_radau (@fpol, [0 20], [2 0], C);
```

to see the effect of using an Jacobian function with the option 'Jacobian'. User defined Jacobian functions must have the form as described before (ie. 'function vr = fjac (vt, vy, varargin)').

'JPattern'

The option 'JPattern' is not handled by any of the solvers by now.

'Vectorized'

The option 'Vectorized' is not handled by any of the solvers by now.

'Mass'

The option 'Mass' can be used to set up an external Mass function or Mass matrix for solving DAE problems. It depends on the solver that is used if 'Mass' is supported or not. It must either be a function handle to a valid function or a full constant matrix of size squared the dimension of the set of differential equations. Run

```
function vdy = frob (t, y, varargin)
    vdy(1,1) = -0.04*y(1)+1e4*y(2)*y(3);
    vdy(2,1) = 0.04*y(1)-1e4*y(2)*y(3)-3e7*y(2)^2;
    vdy(3,1) = y(1)+y(2)+y(3)-1;
```

```
endfunction

function vmas = fmas (vt, vy, varargin)
    vmas = [1, 0, 0; 0, 1, 0; 0, 0, 0];
endfunction
```

```
A = odeset ('Mass', @fmas);
B = oderd (@frob, [0 1e8], [1 0 0], A);
```

to see the effect of using a Mass function with the option 'Mass'. User defined Mass functions must have the form as described before (ie. 'function vmas = fmas (vt, vy, varargin)').

'MStateDependence'

The option 'MStateDependence' can be used to set up the type of the external Mass function for solving DAE problems if a Mass function handle is set with the option 'Mass'. It depends on the solver that is used if 'MStateDependence' is supported or not. It must be a string of the form 'none', 'weak' or 'strong'. Run

```
function vdy = frob (vt, vy, varargin)
    vdy(1,1) = -0.04*vy(1)+1e4*vy(2)*vy(3);
    vdy(2,1) = 0.04*vy(1)-1e4*vy(2)*vy(3)-3e7*vy(2)^2;
    vdy(3,1) = vy(1)+vy(2)+vy(3)-1;
endfunction
```

```
function vmas = fmas (vt, varargin)
    vmas = [1, 0, 0; 0, 1, 0; 0, 0, 0];
endfunction
```

```
A = odeset ('Mass', @fmas, 'MStateDependence', 'none');
B = oderd (@frob, [0 1e8], [1 0 0], A);
```

to see the effect of using a Mass function with the option 'MStateDependence'. User defined Mass functions must have the form as described before (ie. 'function vmas = fmas (vt, varargin)' if the option 'MStateDependence' was set to 'none', otherwise the user defined Mass function must have the form 'function vmas = fmas (vt, vy, varargin)' if the option 'MStateDependence' was set to either 'weak' or 'strong').

'MvPattern'

The option 'MvPattern' is not handled by any of the solvers by now.

'MassSingular'

The option 'MassSingular' is not handled by any of the solvers by now.

'NonNegative'

The option 'NonNegative' is not handled by any of the solvers by now.

'Events'

The option 'Events' can be used to set up an Event function, ie. the Event function can be used to find zero crossings in one of the results. It must either be a function handle to a valid function. Run

```
function vdy = fbal (vt, vy, varargin)
    vdy(1,1) = vy(2)+3;
    vdy(2,1) = -9.81; %# m/s
endfunction
```

```
function [veve, vterm, vdir] = feve (vt, vy, varargin)
```

```
    veve = vy(1); %# Which event component should be tread
    vterm = 1; %# Terminate if an event is found
    vdir = -1; %# In which direction, -1 for falling
endfunction
```

```
A = odeset ('Events', @feve);
B = ode78 (@fbal, [0 1.5], [1 3], A);
plot (B.x, B.y(:,1));
```

to see the effect of using an Events function with the option 'Events'.

'MaxOrder'

The option 'MaxOrder' is not handled by any of the solvers by now.

'BDF'

The option 'BDF' is not handled by any of the solvers by now.

3 Coder's Guide

3.1 C Mex Function Reference

- `void mexFixMsgTxt (const char * vmsg)` [Function]
vmsg: The string that has to be displayed
 Displays the string *vmsg* in the octave window as "FIXME: ..." and continues.
- `void mexUsgMsgTxt (const char * vmsg)` [Function]
vmsg: The string that has to be displayed
 Displays the string *vmsg* in the octave window as "usage: ..." and stops computation because of an empty error message.
- `bool mxIsEqual (const mxArray * vone, const mxArray * vtwo)` [Function]
vone: The first mxArray variable
vtwo: The second mxArray variable
 Compares the two mxArrays *vone* and *vtwo* and returns a boolean value that is either *true* if both mxArrays are the same or *false* if the two mxArrays are different.
Return value: The constant *true* or *false*.
- `bool mxIsVector (const mxArray * vmat)` [Function]
vmat: The numerical mxArray
 Returns a boolean value that is either *true* if *vmat* is a vector or *false* if *vmat* is no vector.
Return value: The constant *true* or *false*.
- `bool mxIsColumnVector (const mxArray * vmat)` [Function]
vmat: The numerical mxArray
 Returns a boolean value that is either *true* if *vmat* is a column vector or *false* if *vmat* is no column vector.
Return value: The constant *true* or *false*.
- `bool mxIsRowVector (const mxArray * vmat)` [Function]
vmat: The numerical mxArray
 Returns a boolean value that is either *true* if *vmat* is a row vector or *false* if *vmat* is no row vector.
Return value: The constant *true* or *false*.
- `bool mxIsMatrix (const mxArray * vmat)` [Function]
vmat: The numerical mxArray
 Returns a boolean value that is either *true* if *vmat* is a numerical matrix or *false* if *vmat* is no matrix.
Return value: The constant *true* or *false*.
- `mxArray * mxGetMatrixRow (mxArray * vmat, unsigned int vind)` [Function]
vmat: The numerical mxArray
 Returns a newly allocated numerical mxArray with one row of elements from the matrix or vector *vmat*.
Return value: An newly allocated mxArray.

`mxArray * mxGetMatrixColumn (mxArray * vmat, unsigned int vind)` [Function]

vmat: The numerical mxArray

Returns a newly allocated numerical mxArray with one column of elements from the matrix or vector *vmat*.

Return value: An newly allocated mxArray.

`mxArray * mxTransposeMatrix (mxArray * vmat)` [Function]

vmat: The numerical mxArray

Returns a newly allocated numerical mxArray matrix that is the non-conjugate transposed matrix of *vmat*.

Return value: An newly allocated mxArray.

Appendix A

A.1 GNU Free Documentation License

Version 1.2, November 2002

Copyright © 2000,2001,2002 Free Software Foundation, Inc.
51 Franklin St, Fifth Floor, Boston, MA 02110-1301, USA

Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document *free* in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or noncommercially. Secondly, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of “copyleft”, which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License in order to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The “Document”, below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as “you”. You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A “Modified Version” of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A “Secondary Section” is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document’s overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The “Invariant Sections” are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The “Cover Texts” are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License.

A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A “Transparent” copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not “Transparent” is called “Opaque”.

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The “Title Page” means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, “Title Page” means the text near the most prominent appearance of the work’s title, preceding the beginning of the body of the text.

A section “Entitled XYZ” means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as “Acknowledgements”, “Dedications”, “Endorsements”, or “History”.) To “Preserve the Title” of such a section when you modify the Document means that it remains a section “Entitled XYZ” according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or noncommercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document’s license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both

covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

- A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.
- B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.
- C. State on the Title page the name of the publisher of the Modified Version, as the publisher.
- D. Preserve all the copyright notices of the Document.
- E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.
- F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.
- G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.
- H. Include an unaltered copy of this License.
- I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its

Title Page, then add an item describing the Modified Version as stated in the previous sentence.

- J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the “History” section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.
- K. For any section Entitled “Acknowledgements” or “Dedications”, Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.
- L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.
- M. Delete any section Entitled “Endorsements”. Such a section may not be included in the Modified Version.
- N. Do not retitle any existing section to be Entitled “Endorsements” or to conflict in title with any Invariant Section.
- O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version’s license notice. These titles must be distinct from any other section titles.

You may add a section Entitled “Endorsements”, provided it contains nothing but endorsements of your Modified Version by various parties—for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled “History” in the various original documents, forming one section Entitled “History”; likewise combine any sections Entitled “Acknowledgements”, and any sections Entitled “Dedications”. You must delete all sections Entitled “Endorsements.”

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an “aggregate” if the copyright resulting from the compilation is not used to limit the legal rights of the compilation’s users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document’s Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled “Acknowledgements”, “Dedications”, or “History”, the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See <http://www.gnu.org/copyleft/>.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License “or any later version” applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

To use this License in a document you have written, include a copy of the License in the document and put the following copyright and license notices just after the title page:

```
Copyright (C) year your name.  
Permission is granted to copy, distribute and/or modify this document  
under the terms of the GNU Free Documentation License, Version 1.2  
or any later version published by the Free Software Foundation;  
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover  
Texts. A copy of the license is included in the section entitled “GNU  
Free Documentation License”.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being list their titles, with  
the Front-Cover Texts being list, and with the Back-Cover Texts  
being list.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.